DATASHEET

Mini-Patchpanel STP 12xRJ45 Cat.6, 10“ 1U, RAL7035 grey



General data

The high quality of the shielded Cat.6 RJ45 mini patch panel ensures excellent performance for 5 Gigabit Ethernet applications. In addition, the mini patch panel is characterized by its versatile mounting options. It is suitable for installation in a **10 "plane**, for **attachment to the wall** or in conjunction with the DIN rail clamp set (Part No. H83030.1) for **DIN rail mounting**.

10 "mounting / wall mounting or DIN rail mounting possible, 1U
12 ports
LSA connection strip for installation cable AWG24..AWG22
Color code according to TIA / EIA 568 A / B
Lid with quick release
With earthing terminal

Scope of delivery:
12 cable ties, assembly instructions
4 screws (M6x16mm) and nut

Tekniske egenskaber

Available variants

ArtNr.	Bezeichnung	Colour	Number of buses/couplings	RAL-number
37736.12	Mini-Patchpanel STP 12xRJ45 Cat.6, 10“ 1U, RAL7035 grey	grey	12	7035

This datasheet was created automatically on 13-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50


info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

Mini-Patchpanel STP 12xRJ45 Cat.6, 10“ 1U, RAL7035 grey

datasheets.content.drawings



Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product’s suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION