

DATASHEET



General data

The high quality of the shielded Cat.6A RJ45 mini patch panel ensures excellent performance for 10 Gigabit Ethernet applications. The **10"** patch panel offers a **high port density** with 8 ports at **0.5 U**. In addition, the mini patch panel is characterized by its versatile mounting options. It is suitable for installation in a **10 "plane**, for **attachment to the wall** or in conjunction with the DIN rail clamp set (Part No. H83030.1) for **DIN rail mounting**.

10 "mounting / wall mounting or DIN rail mounting possible, 1U

8 ports

LSA connection strip for installation cable AWG24..AWG22

Color code according to TIA / EIA 568 A / B

Lid with quick release

With earthing terminal

Scope of delivery:

8 cable ties, assembly instructions

4 screws (M6x16mm) and nut

Tekniske egenskaber

Available variants

This datasheet was created automatically on 22-09-2026 . Technical changes reserved.



DATASHEET

ArtNr.	Bezeichnung	Colour	Number of buses/couplings	RAL-number
37738.8		grey	8	7035

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 22-09-2026 . Technical changes reserved.

