DATASHEET

LSA Overvoltage Arrester 8x13 / 230 V / 10 kA + FailSafe



General data

Gas-filled
Rated discharge current 10 kA

Tekniske egenskaber

Available variants

ArtNr.	Bezeichnung	Frequency	Nominal discharge surge current (8/20)	Nominal load current	Nominal voltage AC	Nominal voltage DC	Pro-active thermo-control	Type
46145.1	LSA Overvoltage Arrester 8x13 / 90 V / 10 kA	3 Hz	10 kA	10000 A	90.0 V	90 V	True	8x13 / 90V / 10kA
46146.1	LSA Overvoltage Arrester 8x13 / 230 V / 10 kA	3 Hz	10 kA	10000 A	250 V	230 V	True	8x13 / 230V / 10kA
46147.1	LSA Overvoltage Arrester 8x13 / 230 V / 10 kA + FailSafe	3 Hz	10 kA	10000 A	250 V	230 V	True	8x13 / 230V / 10kA + Failsave

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION