


DATASHEET



General data

The fiber optic cable with a central, gel-filled loose tube and up to 24 fibers is ideal for structured cabling. Thanks to a high tensile strength of 2000N, it is designed for both indoor and outdoor applications. The dielectric construction with glass yarn reinforcement makes it longitudinally watertight and offers additional protection through a flame-retardant sheath.

It can be used outdoors, when laid directly underground in sand beds or in shafts, and as a flame-retardant cable indoors.

This cable is versatile for LAN and WAN backbones, telecom access lines, fiber-to-business, fiber-to-the-home and access connections.

Features:

- Universal cable for versatile applications
- The sheath is made of halogen-free, flame-retardant material in accordance with IEC 60332-1-2 and Eurofire class Eca.
- Suitable for connector assemblies, supports easy integration into existing networks

This datasheet was created automatically on 22-09-2026 . Technical changes reserved.



DATASHEET

- Metal-free and longitudinally watertight
- Rodent-proof and flame-retardant
- The cable diameter can vary depending on the design and number of fibers
- DIN/VDE: U-DQ(ZN)BH

Tekniske egenskaber

Available variants

ArtNr.	Bezeichnung	CPR-Class	Cable Ø	Category	Number of fibres	Tensile force max.
54504.1D-E2		Eca	5.8 mm	OM3	4	2000 N
54508.1D-E2		Eca	5.8 mm	OM3	8	2000 N
54512.1D-E2		Eca	5.8 mm	OM3	12	2000 N
54524.1D-E2		Eca	5.8 mm	OM3	24	2000 N

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 22-09-2026 . Technical changes reserved.

