


DATASHEET

19" Wall Housing 6U, Swiveling, 2-Part, RAL7035, Depth 600 mm



General data

Steel sheet housing with welded frame, pre-assembled, self-ventilated

Rear sided swing-frame for swiveling the front part of the housing

Prepared for Plug & Play 2-fan unit Art.-No. 691656xx

Bottom with 4 x mounting point for leveling feet or castor set (please order separately)

Front door with metal hinges for increased stability

Pre-punched openings for cable entry optionally from roof or bottom

Prepared for mounting of single fan units in roof and bottom

Inside front-sided 2 x 19" profile rails, galvanised, depth-adjustable

Front door with window made of certified safety glass

Front door lockable with latch

Internal earthing of all cabinet sections

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

DATASHEET

19" Wall Housing 6U, Swiveling, 2-Part, RAL7035, Depth 600 mm

Paint finish: RAL7035, light grey

Protection degree IP20

Included in delivery: 1 x brush terminal, 1 x set of captive nuts (PU 20 pcs.), 2 x key

Delivery in transport packaging, from 30 kg / 12U on disposable pallet

Tekniske egenskaber

Available variants

ArtNr.	Bezeichnung	Colour	Depth	Height	Max. Load	Number of height units	Width	RAL-number
691606VGR.60	19" Wall Housing 6U, Swiveling, 2-Part, RAL7035, Depth 600 mm	grey	600 mm	330 mm	40 kg	6 U	600 mm	7035
691609VGR.60	19" Wall Housing 9U, Swiveling, 2-Part, RAL7035, Depth 600 mm	grey	600 mm	465 mm	40 kg	9 U	600 mm	7035
691612VGR.60	19" Wall Housing 12U, Swiveling, 2-Part, RAL7035, Depth 600 mm	grey	600 mm	600 mm	40 kg	12 U	600 mm	7035
691615VGR.60	19" Wall Housing 15U, Swiveling, 2-Part, RAL7035, Depth 600 mm	grey	600 mm	730 mm	50 kg	15 U	600 mm	7035
691618VGR.60	19" Wall Housing 18U, Swiveling, 2-Part, RAL7035, Depth 600 mm	grey	600 mm	860 mm	50 kg	18 U	600 mm	7035
691621VGR.60	19" Wall Housing 21U, Swiveling, 2-Part, RAL7035, Depth 600 mm	grey	600 mm	997 mm	50 kg	21 U	600 mm	7035

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

