

DATASHEET



General data

One Housing – 3 Mounting Options:
19" 5U vertical – 10" 10U horizontal – 19" 10HE horizontal

- Steel sheet housing, completely pre-assembled
- Front door and left side wall with windows of certified safety glass (4 mm)
- Front door lockable with 1-point latch locking
- Left side wall hinged for easy access
- Right side wall with holes for wall mounting
- Rear wall prepared for mounting of plug & play fan unit Art.-No. 691656GR or single fan Art.-No. 691664
- Inner mounting points for earthing set Art.-No. K3930V2N
- Roof and bottom with pre-punched openings for cable entry (145 x 70 mm)
- Paint finish RAL7035, light grey
- Protection degree IP20
- Included in delivery: 1 x brush strip, 1 x plastic cover, 1 x cage nut set (PU 20 pcs.), keys
- Delivery in transport packaging

Tekniske egenskaber

Available variants

This datasheet was created automatically on 20-09-2026 . Technical changes reserved.



DATASHEET

ArtNr.	Bezeichnung	Colour	Depth	Height	Width
691706VGL.1		grey	682 mm	543 mm	364 mm

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 20-09-2026 . Technical changes reserved.

