


DATASHEET

19" Wall Housing 6U, Fixed, 1-Part, RAL7035, Depth 500 mm



General data

Steel sheet housing with welded frame, completely pre-assembled, self-ventilated

NEW: Prepared for Plug & Play 2-fan unit Art.-No. 691656xx

NEW: Bottom with 4 x mounting point for leveling feet or castor set (please order separately)

NEW: Front door with metal hinges for increased stability

Side walls removable, lockable, locks equal to door lock

Roof, bottom and rear wall with pre-punched openings for cable entry (250 x 70 mm)

Front-sided 2 x 19" profile rails, galvanised, depth-adjustable

Front door with latch locking and window made of certified safety glass (thickness 4 mm)

Internal earthing of all cabinet sections

Paint finish RAL7035, light grey

Protection degree IP20

Included in delivery: 1 x brush terminal, 1 x set of captive nuts (PU 20 pcs.), 2 x key

This datasheet was created automatically on 15-09-2026 . Technical changes reserved.

DATASHEET

19" Wall Housing 6U, Fixed, 1-Part, RAL7035, Depth 500 mm

Delivery in transport packaging, from 30 kg / 12U on disposable pallet

Tekniske egenskaber

Available variants

ArtNr.	Bezeichnung	Colour	Depth	Height	Max. Load	Number of height units	Width	RAL-number
691706VGR.50	19" Wall Housing 6U, Fixed, 1-Part, RAL7035, Depth 500 mm	grey	500 mm	330 mm	50 kg	6 U	600 mm	7035
691709VGR.50	19" Wall Housing 9U, Fixed, 1-Part, RAL7035, Depth 500 mm	grey	500 mm	465 mm	50 kg	9 HE	600 mm	7035
691712VGR.50	19" Wall Housing 12U, Fixed, 1-Part, RAL7035, Depth 500 mm	grey	500 mm	600 mm	50 kg	12 U	600 mm	7035
691715VGR.50	19" Wall Housing 15U, Fixed, 1-Part, RAL7035, Depth 500 mm	grey	500 mm	730 mm	50 kg	15 U	600 mm	7035

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 15-09-2026 . Technical changes reserved.

