

DATASHEET



General data

One Housing - Two Mounting Possibilities: 19" 5U vertical or 10" 10U horizontal

Steel sheet housing 5U vertical, completely pre-assembled
 Front-sided 19" level made of punched profile
 Front door with window made of certified safety glass (thickness 4 mm)
 Front door with latch
 Left side wall hinged for easy access
 Right side wall with holes for wall mounting
 Rear wall prepared for mounting of plug & play fan unit Art.-No. 691656GR.1 or single fans Art.-No. 691664
 Internal earthing of all cabinet sections
 Additional earthing bolt M6 inside the housing
 Pre-punched openings (145 x 70 mm) for cable entry from roof or bottom

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.



DATASHEET

Paint finish RAL7035, light grey
 Protection degree IP20
 Included in delivery: 2 x plastic cover, 2 x key
 Delivery in transport packaging

Tekniske egenskaber

Available variants

ArtNr.	Bezeichnung	Colour	Depth	Height	Max. Load	Max. load capacity	Number of height units	Width
691706VN.1		grey	500 mm	543 mm	50 kg	50 kg	5 U	345 mm

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

