



DATASHEET



General data

Acoustically high-quality insulated wall housing, basing on EFB standard wall housings
For realisation of network projects in SoHo environments and acoustical insulation of loud, active devices like e.g. switches, router etc.

For installation in immediate near of working places, in seminar- or conference rooms without noise pollution

Complete inner lining with especially noise absorbers

Attenuation (typ.) 8 .. 25 dB (frequency-dependent)

Special decoupled Super-Silent fans (evacuating) in roof area

Converted air volume 196 m³/h

Closeable fresh air inlets in bottom

Cable entry in bottom via noise bridge and brush

Front door with window of certified safety glass (4 mm), lockable

Side walls detachable, lockable, lock equal to door lock

Paint finish RAL7035, light grey

Delivery incl. 2 x key, 1 x power supply for the fans

This datasheet was created automatically on 29-09-2026 . Technical changes reserved.

DATASHEET

All EFB housings are available as acoustical insulated type - ask your sales contact!

Tekniske egenskaber

Available variants

ArtNr.	Bezeichnung	Colour	Depth	Height	Max. Load	Number of height units	Width
691709.1-AK		grey	500 mm	465 mm	50 kg	9 HE	600 mm

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 29-09-2026 . Technical changes reserved.

