

DATASHEET

19" Wall Housing Flat Pack 9U, Depth 600 mm, RAL9005



General data

Steel sheet housing with screwed frame
 Not pre-assembled, self-ventilated
 Side wall removable with quick fastener
 Roof, bottom and rear wall with pre-punched openings for cable entry (230 x 41 mm)
 Roof prepared for mounting of 2 x single fan (Art.-No. 691664)
 Inside 2 x 19" rails front-sided, depth-adjustable
 Front door with window of certified safety glass with lock (thickness 4 mm)
 Cabinet parts completely earthed
 Max. load 60 kg
 Protection degree IP20
 Paint finish RAL9005, jet black
 Included accessories: 2 x key

This datasheet was created automatically on 10-10-2026 . Technical changes reserved.



DATASHEET

19" Wall Housing Flat Pack 9U, Depth 600 mm, RAL9005

Delivery unassembled in transport packaging (1 carton)

Tekniske egenskaber

Available variants

ArtNr.	Bezeichnung	Colour	Depth	Height	Max. Load	Number of height units	Width	RAL-number
691709FTS.2	19" Wall Housing Flat Pack 9U, Depth 600 mm, RAL9005	Black	600 mm	500 mm	60 kg	9 HE	570 mm	9005
691712FTS.2	19" Wall Housing Flat Pack 12U, Depth 600 mm, RAL9005	Black	600 mm	635 mm	60 kg	12 U	570 mm	9005
691715FTS.2	19" Wall Housing Flat Pack 15U, Depth 600 mm, RAL9005	Black	600 mm	770 mm	60 kg	15 U	570 mm	9005
691721FTS.2	19" Wall Housing Flat Pack 21U, Depth 600 mm, RAL9005	Black	600 mm	1040 mm	60 kg	21 U	570 mm	9005

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 10-10-2026 . Technical changes reserved.

