
# DATASHEET

## 19" Wall Housing 9U, Fixed, 1-Part, RAL7035, Depth 400 mm














### General data

Steel sheet housing with welded frame, completely pre-assembled, self-ventilated
**NEW: Prepared for Plug & Play 2-fan unit Art.-No. 691656xx**
**NEW: Bottom with 4 x mounting point for leveling feet or castor set (please order separately)**
**NEW: Front door with metal hinges for increased stability**
Side walls removable, lockable, locks equal to door lock
Roof, bottom and rear wall with pre-punched openings for cable entry (250 x 70 mm)
Front-sided 2 x 19“ profile rails, galvanised, depth-adjustable
Front door with latch locking and window made of certified safety glass (thickness 4 mm)
Internal earthing of all cabinet sections
Paint finish RAL7035, light grey
Protection degree IP20
Included in delivery: 1 x brush terminal, 1 x set of captive nuts (PU 20 pcs.), 2 x key

**This datasheet was created automatically on 01-11-2026 . Technical changes reserved.**

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

# DATASHEET

## 19" Wall Housing 9U, Fixed, 1-Part, RAL7035, Depth 400 mm

Delivery in transport packaging, from 30 kg / 12U on disposable pallet

### Tekniske egenskaber

### Available variants

| ArtNr. | Bezeichnung | Colour | Depth | Height | Max. Load | Number of height units | Width | RAL-number |
|---|---|---|---|---|---|---|---|---|
| 691704VGR.40 | 19" Wall Housing 4U, Fixed, 1-Part, RAL7035, Depth 400 mm | grey | 400 mm | 240 mm | 50 kg | 4 U | 600 mm | 7035 |
| 691706VGR.40 | 19" Wall Housing 6U, Fixed, 1-Part, RAL7035, Depth 400 mm | grey | 400 mm | 330 mm | 50 kg | 6 U | 600 mm | 7035 |
| 691709VGR.40 | 19" Wall Housing 9U, Fixed, 1-Part, RAL7035, Depth 400 mm | grey | 400 mm | 465 mm | 50 kg | 9 U | 600 mm | 7035 |
| 691712VGR.40 | 19" Wall Housing 12U, Fixed, 1-Part, RAL7035, Depth 400 mm | grey | 400 mm | 600 mm | 50 kg | 12 U | 600 mm | 7035 |

**Note on Intended Use**

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

**This datasheet was created automatically on 01-11-2026 . Technical changes reserved.**

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION