




DATASHEET



General data

Acoustically high-quality insulated wall housing, basing on EFB standard wall housings
 For realisation of network projects in SoHo environments and acoustical insulation of loud, active devices like e.g. switches, router etc.
 For installation in immediate near of working places, in seminar- or conference rooms without noise pollution
 Complete inner lining with especially noise absorbers
 Attenuation (typ.) 8 .. 25 dB (frequency-dependent)
 Special decoupled Super-Silent fans (evacuating) in roof area
 Converted air volume 196 m³/h
 Closeable fresh air inlets in bottom
 Cable entry in bottom via noise bridge and brush
 Front door with window of certified safety glass (4 mm), lockable
 Side walls detachable, lockable, lock equal to door lock
 Paint finish RAL7035, light grey
 Delivery incl. 2 x key, 1 x power supply for the fans

This datasheet was created automatically on 17-09-2026 . Technical changes reserved.

DATASHEET

All EFB housings are available as acoustical insulated type - ask your sales contact!

Tekniske egenskaber

Available variants

ArtNr.	Bezeichnung	Colour	Depth	Height	Max. Load	Number of height units	Width
691712.1-AK		grey	500 mm	600 mm	50 kg	12 U	600 mm

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 17-09-2026 . Technical changes reserved.

