
DATASHEET

19" Wall Housing IP55, 12U, Glass Door, Depth 600 mm, RAL7035









General data

Steel sheet housing with welded corpus, completely pre-assembled
Right- and left-sided metal covered air inlets for passive ventilation
Side walls not detachable
Roof hinged, inner roof prepared for mounting of Plug&Play fan unit Art.-No. 691656GR (cable not included, please order separately, e.g. Art.-No. EK504.x)
Bottom with PG glands 1 x PG48, 2 x PG21 and 3 x Ø 20 mm PVC blind grommets
For depth 450 mm inside 2 x 19" profile rails front-sided, galvanised, with numberung of rack units (U)
For depth 600 mm inside 4 x 19" profile rails (2 front, 2 rear), galvanised, with numberung of rack units (U)
Front door with window of certified safety glass and 3-point bar locking, lockable, with profile half-cylinder acc. to DIN 18252 / EN1303
Profile half-cylinder exchangeable by customer
Cabinet parts inside completely earthed
Max. load 100 kg
Paint finish RAL7035, light grey
Protection degree IP55
Plinth for use as standing cabinet available as option
Included accessories: 4 x Wall mount angle, 2 x key

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

19" Wall Housing IP55, 12U, Glass Door, Depth 600 mm, RAL7035

Tekniske egenskaber

Available variants

ArtNr.	Bezeichnung	Colour	Depth	Height	Max. Load	Max. load capacity	Number of height units	Width	RAL-number
691707IP55.2G	19" Wall Housing IP55, 7U, Glass Door, Depth 600 mm, RAL7035	grey	600 mm	450 mm	100 kg	100 kg	7 U	600 mm	7035
691709IP55.2G	19" Wall Housing IP55, 9U, Glass Door, Depth 600 mm, RAL7035	grey	600 mm	540 mm	100 kg	100 kg	9 U	600 mm	7035
691712IP55.2G	19" Wall Housing IP55, 12U, Glass Door, Depth 600 mm, RAL7035	grey	600 mm	670 mm	100 kg	100 kg	12 U	600 mm	7035
691716IP55.2G	19" Wall Housing IP55, 16U, Glass Door, Depth 600 mm, RAL7035	grey	600 mm	850 mm	100 kg	100 kg	16 U	600 mm	7035
691720IP55.2G	19" Wall Housing IP55, 20U, Glass Door, Depth 600 mm, RAL7035	grey	600 mm	1040 mm	100 kg	100 kg	20 U	600 mm	7035

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION