DATASHEET

Cat.7 Outdoor cable UC900 SS23/1,4P PE, 100metres









General data

The data cable is an installation cable with a thick-walled polyethylene outer sheath, suitable for **direct burial**, **UV-resistant** and for transmission rates up to **1000 MHz**. Exeeds the electrical transmission properties and requirements of the category 7 and lower. Suitable for structured cabling of Class E, EA, F and according to ISO/IEC11801 (AMD 2:2009) resp. EN50173-1 (2009). With this cable transmission rates up to 10 GBit according to IEEE 802.3 are possible.

Tekniske egenskaber

Available variants

ArtNr.	Bezeichnung	Colour outer sheath	Length	Number of cores	RAL colour	Type	Copper weight	Weight	Max. tractive force	Outer diameter approx.
99731.100	Cat.7 Outdoor cable UC900 SS23/1,4P PE, 100metres	black	100.0 m	8	RAL 9005	simplex	38 kg/km	95 kg/km	340 N	8.4 mm
99731.500	Cat.7 Outdoor cable UC900 SS23/1,4P PE, 500metres	black	500.0 m	8	RAL 9005	simplex	38 kg/km	95 kg/km	340 N	8.4 mm

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 21-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION