

DATASHEET













General data

This fiber optic cable with a central, gel-filled loose tube and up to 24 fibers is ideal for outdoor applications in modern telecommunications networks. Its dielectric construction with glass yarn armoring makes it longitudinally watertight and resistant to mechanical stress. A robust LDPE outer jacket further protects the cable from environmental influences.

It can be installed outdoors – directly in the ground (in a sand bed), in pipes, or shafts. Thanks to its metal-free and rodent-resistant design, it is particularly durable and reliable under demanding conditions.

This cable is versatile for LAN and WAN backbones, telecom access lines, fiber-to-business, fiber-to-the-building, and fiber-to-the-home drop and access connections.

Features:

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

- Robust outdoor cable for versatile applications
- Dielectric construction with glass yarns – completely metal-free
- Gel-filled, stranded loose tubes with up to 288 fibers
- Longitudinally watertight
- UV- and weather-resistant LDPE jacket
- Suitable for direct burial in sand beds
- Rodent-resistant and resistant to tensile loads
- DIN/VDE: A-DQ(ZN)B2Y

Tekniske egenskaber

Available variants

ArtNr.	Bezeichnung	Cable Ø	Category	Number of fibres	Tensile force max.
A12M4F1		5.8 mm	OM4	12	2000 N
A24M4F1		5.8 mm	OM4	24	2000 N
A4M4F1		5.8 mm	OM4	4	2000 N
A8M4F1		5.8 mm	OM4	8	2000 N

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de