

DATASHEET















General data

The pull-out splice box from EFB-Elektronik is designed for the structured pick-up of splices and the clear management of single-mode fibre optic connections in a 19-inch rack. The solution is designed for OS2 according to ITU-T G.652.D and combines a pre-assembled assembly with SC duplex couplings with a service-friendly, pull-out design.

• 1U pull-out design for 19" installation – Allows for compact integration in the rack and makes it easy to access the splice level during maintenance.
• Front panel with 6 SC duplex couplings and 6 blanking plugs – Ensures clean, pre-assembled assembly and keeps unused positions neatly sealed.
• 12 prepared SC pigtails with LSZH jacket and 2 m length – Support efficient splicing organisation and reduce installation effort.

The sheet steel housing in grey according to RAL 7035 is designed for clean routing of the fibre optic lines. The OS2 fibre class according to ITU-T G.652.D, the vertical arrangement of the couplings and the ceramic ferrule guide

This datasheet was created automatically on 03-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

support the use in professional single-mode installations. Pre-assembled crimp/ANT splice holders and enclosed shrink splice holders enable flexible splice organisation. The pigtails are prepared as a loose-buffered version with LSZH coating, 0.9 mm diameter and blue connector.

Technical details
- Extendable: Yes
- Fibre class: OS2 according to ITU-T G.652.D
- Couplings: SC-Duplex
- With number of couplings/adapters: 6
- Coupling material: plastic
- Pigtail: 12 x SC
- Pigtails prepared: discontinued
- Alignment of the couplings/adapters: vertical
- Colour: grey
- Material: sheet steel
- Couplings (ferrule guide): Ceramic
- Coupling colour: blue
- Mounting type: 482.6 mm (19 in) Installation
- With front panel: Yes
- With housing: Yes
- With pigtails: Yes
- Pigtail Buffer Type: Loose-Buffered
- Pigtail Coating Material: LSZH
- Pigtail diameter: 0.9 mm
- Pigtail Colour: DIN
- Pigtail length: 2 m
- Pigtail connector colour: blue

Tekniske egenskaber

Available variants

ArtNr.	Bezeichnung	Colour	Pigtail	Suitable for number of couplings/adapters	Type of connector external	With number of couplings/adapters
BA71223L12		grey	12 x SC	12	SC-Duplex	6
BA71223L24		grey	24 x SC	12	SC-Duplex	12

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 03-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION