DATASHEET









General data

For 10G Ethernet Data Center Intra-Rack and Inter-Rack links
Hot-pluggable SFP+ cable ends
Rigid pull-tab for improved high-density installations
Supports 10.3125 Gb/s bit rate
RoHS-6 compliant (lead-free)
SFI limiting interface
Single 3.3V power supply
Low power dissipation
Commercial temperature range: 0° C to 70° C

Tekniske egenskaber

This datasheet was created automatically on 08-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

Available variants

ArtNr.	Bezeichnung	Length
BO353503J10M-BO		10.0 m
BO353503J1M-BO		1.0 m
BO353503J3M-BO		3.0 m

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 08-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION