

DATASHEET



General data

D-Link DEM-432XT compatible 10GBASE-LR SFP+ transceiver with LC duplex connection according to MSA standards from the BlueOptics brand. The D-Link DEM-432XT compatible 10GBASE-LR LC Duplex SFP+ has a receiving function (receiver with 1310nm) and a transmitting function (transmitter with 1310nm) for the transmission of optical signals via single-mode fiber optic, taking into account the respective transmission protocol. This D-Link DEM-432XT compatible 10GBASE-LR LC Duplex SFP+ is suitable for use in all common hardware platforms (such as switches, routers, storage systems, load balancers, measuring devices, etc.) that also support the original D-Link DEM -432XT 10GBASE-LR LC Duplex SFP+ officially support. Each D-Link DEM-432XT compatible 10GBASE-LR LC Duplex SFP+ supports Ethernet, Fiber Channel over Ethernet or SDH/SONET high-speed applications of up to 10G per second.

Tekniske egenskaber

Available variants

ArtNr.	Bezeichnung	Unique
DEM-432XT-BO		Unique

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 11-09-2026 . Technical changes reserved.

