

DATASHEET

MTP/MPO Trunkcable OM3 12 fibers Type A LSZH turquoise 10m



General data

MTP/MPO Trunk Cable designed for Data Centers, High Speed Ethernet. High density and scalability. MTP/MPO are designed with a form factor like other standard Fiber Optic connectors like LC, SC but with a high density based on a matrix of 12 fiber.

The cables provide a Low loss connection with an Insertion Loss "IL" at maximum 0,35db and a return loss of minimum 30db

Tekniske egenskaber

Available variants

ArtNr.	Bezeichnung	Length	Number of fibres
DK-12FTC45OM3.10	MTP/MPO Trunkcable OM3 12 fibers Type A LSZH turquoise 10m	10 m	12
DK-12FTC45OM3.12	MTP/MPO Trunkcable OM3 12 fibers Type A LSZH turquoise 12m	12 m	12
DK-12FTC45OM3.15	MTP/MPO Trunkcable OM3 12 fibers Type A LSZH turquoise 15m	15 m	12
DK-12FTC45OM3.20	MTP/MPO Trunkcable OM3 12 fibers Type A LSZH turquoise 20m	20 m	12
DK-12FTC45OM3.25	MTP/MPO Trunkcable OM3 12 fibers Type A LSZH turquoise 25m	25 m	12
DK-12FTC45OM3.5	MTP/MPO Trunkcable OM3 12 fibers Type A LSZH turquoise 5m	5 m	12
DK-12FTC45OM3.7	MTP/MPO Trunkcable OM3 12 fibers Type A LSZH turquoise 7m	7 m	12

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 21-09-2026 . Technical changes reserved.

