

DATASHEET

MTP/MPO Trunkcable OM4 12 fibers Type A LSZH magenta 10m



General data

MTP/MPO Trunk Cable designed for Data Centers, High Speed Ethernet. High density and scalability. MTP/MPO are designed with a form factor like other standard Fiber Optic connectors like LC, SC but with a high density based on a matrix of 12 fiber.

The cables provide a Low loss connection with an Insertion Loss "IL" at maximum 0,35db and a return loss of minimum 30db

Tekniske egenskaber

Available variants

ArtNr.	Bezeichnung	Length	Number of fibres
DK-12FTC45OM4.10	MTP/MPO Trunkcable OM4 12 fibers Type A LSZH magenta 10m	10 m	12
DK-12FTC45OM4.15	MTP/MPO Trunkcable OM4 12 fibers Type A LSZH magenta 15m	15 m	12
DK-12FTC45OM4.20	MTP/MPO Trunkcable OM4 12 fibers Type A LSZH magenta 20m	20 m	12
DK-12FTC45OM4.25	MTP/MPO Trunkcable OM4 12 fibers Type A LSZH magenta 25m	25 m	12
DK-12FTC45OM4.5	MTP/MPO Trunkcable OM4 12 fibers Type A LSZH magenta 5m	5 m	12
DK-12FTC45OM4.7	MTP/MPO Trunkcable OM4 12 fibers Type A LSZH magenta 7m	7 m	12

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 15-09-2026 . Technical changes reserved.

