# DATASHEET

## MTP/MPO Cassette OM3 1xMPO to 12xLC turquoise Type A



### General data

- MTP/ MPO-Male Fanout Cassette, converting one or two MTP/MPO to LC or SC-adapters
LowLoss description means: attenuation per cassette max. 0,35dB
- MTP/ MPO adapters
- Quick lock
- Colour RAL9005

### Tekniske egenskaber

### Available variants

| ArtNr. | Bezeichnung | Number of connectors connection 1 | Number of connectors connection 2 | Number of fibres |
|---|---|---|---|---|
| DK-819LC12OM3 | MTP/MPO Cassette OM3 1xMPO to 12xLC turquoise Type A | 1 | 6 | 12 |
| DK-819LC12OM3-X | MTP/MPO Cassette OM3 1xMPO to 12xLC turquoise Type C | 1 | 6 | 12 |

**Note on Intended Use**

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

**This datasheet was created automatically on 22-11-2026 . Technical changes reserved.**

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION