DATASHEET





General data

Type-C Malex1 (connect Type-C host)
Type-A Female (connect Type-A device)
Compatible with USB 3.2 Gen2, max 10Gbps, downward compatible with lower versions (USB3.0, USB2.0)
Support max 10m distance
Supports max 5V/900mA downstream charging for connected Type-C device

Note:

1) To achieve max 10Gbps bandwidth, both Type-C host and device should support 10Gbps data transmission.

Tekniske egenskaber

Available variants

ArtNr.	Bezeichnung	Colour	Length
EBUSBC-USBA10GE.5		black	5.0 m

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

regulatory requirements.

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION