# DATASHEET





## General data

USB4 Gen 2x2 cable for connection as data, video and charging cable
20Gbit/s bandwidth
Compatible with USB4, USB 3.2, USB 2.0 and Thunderbolt™ 3
USB Power Delivery 3.0 with up to 100W
DP Alternate mode 2.0 and 1.4 for video output with video resolution up to max. 8K60Hz or 4K120Hz
Supports HDR10, HDCP 1.4 and 2.3
With E-Mark chip for safe power supply

## Tekniske egenskaber

## Available variants

| ArtNr. | Bezeichnung | Colour | Length |
|---|---|---|---|
| EBUSBC40-20G.2 | | black | 2.0 m |

**Note on Intended Use**

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

**This datasheet was created automatically on 19-11-2026 . Technical changes reserved.**

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION