
DATASHEET

Power Cable UK BS1363A - C7 180°, Black, 3.0 m, 2 x 0.75 mm²







General data

2.5 A / 250 V with fuse 3 A
Suitable for UK, Ireland, Singapur, Malaysia

Tekniske egenskaber

Available variants

ArtNr.	Bezeichnung	Colour outer sheath	Length	Nominal current	Nominal voltage	Reaction-to-fire class according to EN 13501-6	Nominal cross section conductor	Outer diameter approx.
EK498.1,8	Power Cable UK BS1363A - C7 180°, Black, 1.8 m, 2 x 0.75 mm²	black	1.8 m	2.5 A	250 V	Dca	0.75 mm²	3.5x5.7 mm
EK498.3	Power Cable UK BS1363A - C7 180°, Black, 3.0 m, 2 x 0.75 mm²	black	3.0 m	2.5 A	250 V	Dca	0.75 mm²	3.5x5.7 mm

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

Power Cable UK BS1363A - C7 180°, Black, 3.0 m, 2 x 0.75 mm²

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION