
DATASHEET

Power Cable UK BS1363A - C13 180°, Black, 3.0 m, 3 x 1.00 mm²







General data

5 A / 250 V with fuse 5 A
Suitable for UK, Ireland, Singapur, Malaysia

Tekniske egenskaber

Available variants

ArtNr.	Bezeichnung	Colour outer sheath	Length	Nominal current	Nominal voltage	Reaction-to-fire class according to EN 13501-6	Nominal cross section conductor	Outer diameter approx.
EK500.2	Power Cable UK BS1363A - C13 180°, Black, 2.0 m, 3 x 0.75 mm²	black	2.0 m	10 A	250 V	Dca	0.75 mm²	6.8 mm
EK500.3	Power Cable UK BS1363A - C13 180°, Black, 3.0 m, 3 x 1.00 mm²	black	3.0 m	10 A	250 V	Dca	1.00 mm²	7.1 mm

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

Power Cable UK BS1363A - C13 180°, Black, 3.0 m, 3 x 1.00 mm²

EK500.5	Power Cable UK BS1363A - C13 180°, Black, 5.0 m, 3 x 1.00 mm²	black	5.0 m	10 A	250 V	Dca	1.00 mm²	7.1 mm

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION