


DATASHEET

Power Cable UK BS1363A - C13 180°, Black, 3.0 m, 3 x 1.00 mm²



General data

5 A / 250 V with fuse 5 A
Suitable for UK, Ireland, Singapur, Malaysia

Tekniske egenskaber

Available variants

ArtNr.	Bezeichnung	Colour outer sheath	Length	Nominal current	Nominal voltage	Reaction-to-fire class according to EN 13501-6	Nominal cross section conductor	Outer diameter approx.
EK500.2	Power Cable UK BS1363A - C13 180°, Black, 2.0 m, 3 x 0.75 mm ²	black	2.0 m	10 A	250 V	Dca	0.75 mm ²	6.8 mm
EK500.3	Power Cable UK BS1363A - C13 180°, Black, 3.0 m, 3 x 1.00 mm ²	black	3.0 m	10 A	250 V	Dca	1.00 mm ²	7.1 mm

This datasheet was created automatically on 13-09-2026 . Technical changes reserved.



DATASHEET

Power Cable UK BS1363A - C13 180°, Black, 3.0 m, 3 x 1.00 mm²

EK500.5	Power Cable UK BS1363A - C13 180°, Black, 5.0 m, 3 x 1.00 mm ²	black	5.0 m	10 A	250 V	Dca	1.00 mm ²	7.1 mm
---------	--	-------	-------	------	-------	-----	----------------------	--------

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 13-09-2026 . Technical changes reserved.

