DATASHEET

Power Cable CEE7/7 90° - Open End WES, 5.0 m, 3 x 1.00 mm²



General data

16 A / 250 V VDE tested
Open End assembled with wire end sleeves
Wire end sleeves for 1.8 m: L = 6 mm, ⌀ 1.7 mm, yellow insulator
Wire end sleeves for 3 + 5 m: L = 8 mm, ⌀ 1.7 mm, red insulator
Cable colour black
Suitable for Germany, Belgium, France and further

Tekniske egenskaber

Available variants

ArtNr.	Bezeichnung	Colour outer sheath	Length	Nominal current	Nominal voltage	Reaction-to-fire class according to EN 13501-6	With protective conductor	Nominal cross section conductor	Outer diameter approx.
EK504AE.1,8	Power Cable CEE7/7 90° - Open End WES, 1.8 m, 3 x 0.75 mm²	black	1.8 m	16 A	250 V	Dca	Ja	0.75 mm²	6.8 mm
EK504AE.3	Power Cable CEE7/7 90° - Open End WES, 3.0 m, 3 x 1.00 mm²	black	3.0 m	16 A	250 V	Dca	Ja	1.00 mm²	7.1 mm

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

Power Cable CEE7/7 90° - Open End WES, 5.0 m, 3 x 1.00 mm²

EK504AE.5	Power Cable CEE7/7 90° - Open End WES, 5.0 m, 3 x 1.00 mm²	black	5.0 m	16 A	250 V	Dca	Ja	1.00 mm²	7.1 mm

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION