

DATASHEET

Extension Cable C14 180° - C13 180°, Grey, 1.8 m, 3 x 0.75 mm²



General data

Plug IEC60320/C14 to jack IEC60320/C13
10 A / 250 V VDE tested

Tekniske egenskaber

Available variants

ArtNr.	Bezeichnung	Colour outer sheath	Length	Nominal current	Nominal voltage	Reaction-to-fire class according to EN 13501-6	Nominal cross section conductor	Outer diameter approx.
EK507.1,8	Extension Cable C14 180° - C13 180°, Grey, 1.8 m, 3 x 0.75 mm ²	grey	1.8 m	10 A	250 V	Dca	0.75 mm ²	6.8 mm
EK507.3	Extension Cable C14 180° - C13 180°, Grey, 3.0 m, 3 x 1.00 mm ²	grey	3.0 m	10 A	250 V	Dca	1.00 mm ²	7.1 mm
EK507.5	Extension Cable C14 180° - C13 180°, Grey, 5.0 m, 3 x 1.00 mm ²	grey	5.0 m	10 A	250 V	Dca	1.00 mm ²	7.1 mm

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 17-09-2026 . Technical changes reserved.

