


DATASHEET

Extension Cable C20 180° - C19 180°, Black, 1.0 m, 3 x 1.50 mm²



General data

Plug IEC60320/C20 to jack IEC60320/C19
16 A / 250 V VDE tested

Tekniske egenskaber

Available variants

ArtNr.	Bezeichnung	Colour outer sheath	Degree of protection	Length	Nominal current	Nominal voltage	Nominal cross section conductor	Outer diameter approx.
EK519.1	Extension Cable C20 180° - C19 180°, Black, 1.0 m, 3 x 1.50 mm ²	black	IP20	1.0 m	16 A	250 V	1.50 mm ²	8.6 mm
EK519.1,8	Extension Cable C20 180° - C19 180°, Black, 1.8 m, 3 x 1.50 mm ²	black	IP20	1.8 m	16 A	250 V	1.50 mm ²	8.6 mm
EK519.2,5	Extension Cable C20 180° - C19 180°, Black, 2.5 m, 3 x 1.50 mm ²	black	IP20	2.5 m	16 A	250 V	1.50 mm ²	8.6 mm
EK519.5	Extension Cable C20 180° - C19 180°, Black, 5.0 m, 3 x 1.50 mm ²	black	IP20	5.0 m	250 V	1.50 mm ²	8.6 mm	

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and

This datasheet was created automatically on 16-09-2026 . Technical changes reserved.



DATASHEET

Extension Cable C20 180° - C19 180°, Black, 1.0 m, 3 x 1.50 mm²

regulatory requirements.

This datasheet was created automatically on 16-09-2026 . Technical changes reserved.

