
# DATASHEET

## Power Cable CEE7/7 180° - C13 90°, Black, 2.0 m, 3 x 0.75 mm²



### General data

10 A / 250 V VDE tested
Suitable for Germany, Belgium, France and further

### Tekniske egenskaber

### Available variants

| ArtNr. | Bezeichnung | Colour outer sheath | Length | Nominal current | Nominal voltage | Reaction-to-fire class according to EN 13501-6 | Nominal cross section conductor | Outer diameter approx. |
|---|---|---|---|---|---|---|---|---|
| EK534.2 | Power Cable CEE7/7 180° - C13 90°, Black, 2.0 m, 3 x 0.75 mm² | black | 2.0 m | 10 A | 250 V | Dca | 0.75 mm² | 6.8 mm |
| EK534.3 | Power Cable CEE7/7 180° - C13 90°, Black, 3.0 m, 3 x 1.00 mm² | black | 3.0 m | 10 A | 250 V | Dca | 1.00 mm² | 7.1 mm |
| EK534.5 | Power Cable CEE7/7 180° - C13 90°, Black, 5.0 m, 3 x 1.00 mm² | black | 5.0 m | 10 A | 250 V | Dca | 1.00 mm² | 7.1 mm |

**Note on Intended Use**

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

**This datasheet was created automatically on 01-11-2026 . Technical changes reserved.**

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION