DATASHEET

Data outlet Cat.6A 500MHz, Surface, 2xRJ45, RAL9010















General data

40°-outlet, LSA IDC terminals, incl. 6.3 mm Grounding connection. Full shielded aluminium die-cast housing, labeling field with transparent cover. For installation in ducts and underfloor systems, central plate conform to DIN49075, metal frame. Design-capable, compatible with all common switch programmes. Incl. surface frame 80 x 80 x 40 mm

Tekniske egenskaber

Available variants

ArtNr.	Bezeichnung	Depth of device	Height of device	Supply line for installation cable	Width of device	Colour
ET-25133AV5-R	Data outlet Cat.6A 500MHz, Surface, 2xRJ45, RAL9010	48 mm	50 mm	Up/down	50 mm	white

This datasheet was created automatically on 23-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

Data outlet Cat.6A 500MHz, Surface, 2xRJ45, RAL9010

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 23-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION