


DATASHEET

Data outlet Cat.6 250MHz, up/down, Flush, 2xRJ45, RAL9010



Class E



General data

Cat.6 (250 MHz) according to ISO/IEC 11801 and EN50173
 40° outlet, 8-pole IDC terminals
 Fully shielded diecast housing
 Labelling field with transparent cover
 For installation in ducts and underfloor systems
 Central plate according to DIN49075
 Central plate 50 x 50 mm, including cover plate 80 x 80 mm
 Design capable, compatible with all common switch programmes

Tekniske egenskaber

This datasheet was created automatically on 17-09-2026 . Technical changes reserved.



DATASHEET

Data outlet Cat.6 250MHz, up/down, Flush, 2xRJ45,
RAL9010

Available variants						
ArtNr.	Bezeichnung	Depth of device	Height of device	Supply line for installation cable	Width of device	Colour
ET-25211.1V1	Data outlet Cat.6 250MHz, up/down, Flush, 2xRJ45, RAL9010	40.95 mm	50 mm	Up/down	50 mm	white
ET-25211.2V1		40.95 mm	50 mm	Left/right	50 mm	

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 17-09-2026 . Technical changes reserved.

