
DATASHEET











General data

Cat.6 (250 MHz) according to ISO/IEC 11801 and EN50173
40° outlet, 8-pole IDC terminals
Fully shielded diecast housing
Labelling field with transparent cover
For installation in ducts and underfloor systems
Central plate according to DIN49075
Central plate 50 x 50 mm, including cover plate 80 x 80 mm
Design capable, compatible with all common switch programmes

Tekniske egenskaber

Available variants

ArtNr.	Bezeichnung	Depth of device	Height of device	Supply line for installation cable	Width of device	Colour
ET-25211.1V1	Data outlet Cat.6 250MHz, up/down, Flush, 2xRJ45, RAL9010	40.95 mm	50 mm	Up/down	50 mm	white
ET-25211.2V1		40.95 mm	50 mm	Left/right	50 mm	

This datasheet was created automatically on 02-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 02-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION