DATASHEET

SFP SM 1000LX 10km SFP, 1310nm 1.25G -40..85°C, LC



General data

This SFP transceiver of the brand Finisar is a multirate SFP for Gigabit Ethernet (1,25 Gbit/s) and Fiber Channell (1,06 Gbit/s). Additionally the transceiver features digital diagnostic functions and has an extended temperature range of -40°C up to 85°C.

Up to 1,25 Gbit/s
Hot-pluggable SFP
Integrated digital diagnostic
1310nm Fabry-Perot laser
LC duplex mating face
Up to 10km over 9/125µm singlemode fiber
Low power consumption <600mW tylical
Extended temperature range -40 up to +85°C
RoHS compliant

Tekniske egenskaber

Available variants

ArtNr.	Bezeichnung	Unique
FTLF1318P3BTL	SFP SM 1000LX 10km SFP, 1310nm 1.25G -40..85°C, LC	Unique

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 02-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION