DATASHEET

MiniGBIC MM 1000SX 550m SFP, 850nm 1.25G -20..85°C, LC



General data

Multirate SFP (mini GBIC) for Gigabit Ethernet and 1 Gbit/s or 2 Gbit/s Fiber Channel to Multimode
Technical Data
Up to 2,125 Gbit/s
Hot-pluggable SFP
Integrated digital diagnostic
850nm VCSEL Laser
LC duplex mating face
Up to 500m over 50/125µm Fiber, 300m over 62,5/125µm Fiber
Metalhousing for good EMC
3,3V power supply
Low power consumption
extended temperature range of -20°C up to 85°C
Applications
1,25 Gbit/s 1000Base-SX Ethernet
Dual Rate 1,063/2,125 Gbit/s FiberChannel
RoHS compliant

Tekniske egenskaber

Available variants

ArtNr.	Bezeichnung	Unique
FTLF8519P3BNL	MiniGBIC MM 1000SX 550m SFP, 850nm 1.25G -20..85°C, LC	Unique

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a

This datasheet was created automatically on 29-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 29-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION