

DATASHEET

MiniGBIC MM 10GBase SFP+, LC, OM2/82m - OM3/300m - OM4/400m



General data

Up to 10.5 Gbit/s rate
 Hot-pluggable SFP+
 DDM function, Digital Diagnostics Monitoring
 integrated digital diagnostic
 850nm Oxide VCSEL Laser
 Duplex LC connector
 RoHS conform
 Up to 400m with 50/125µm optical fibre (OM4)
 Up to 300m with 50/125µm optical fibre (OM3)
 Up to 82m with 50/125µm optical fibre (OM2)
 Metallic housing for low electromagnetic radiation
 3,3V power supply
 Temperatur area -5°C to +70°C
 10,5 Gbit/s 10GBase-SR Ethernet

Tekniske egenskaber

Available variants

ArtNr.	Bezeichnung	Unique
FTLX8574D3BCL	MiniGBIC MM 10GBase SFP+, LC, OM2/82m - OM3/300m - OM4/400m	Unique

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 19-09-2026 . Technical changes reserved.

