


DATASHEET



General data

The UC Home FTTH indoor cable offers 4 BendBrightXS fibers and is designed for the highest flame retardancy. It is ideal for indoor installation and blowing techniques in public buildings.

Features:

- Flame retardancy: Very high flame retardancy for maximum safety
- Installation options: Suitable for indoor installation and blowing techniques
- Area of application: Public buildings
- CPR classification: Class B2ca s1a d1 a1, ensures:
 - o B2ca: High flame retardancy
 - o s1a: Very low smoke development
 - o d1: No burning droplets
 - o a1: No acid formation

This datasheet was created automatically on 17-09-2026 . Technical changes reserved.



DATASHEET

This cable is perfect for demanding FTTH installations in environments that have the highest safety and performance requirements.

Delivery: 500m spool

Tekniske egenskaber

Available variants

ArtNr.	Bezeichnung	CPR-Class	Cable Ø	Category	Number of fibres	Tensile force max.
FTTH-IDROP250-4-B2		B2ca	2.3 mm	OS2	4	400 N

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 17-09-2026 . Technical changes reserved.

