

DATASHEET



General data

The UC Home FTTH indoor cable is equipped with 2 or 4 BendBrightXS fibers and is specifically designed for optical subscriber access. It offers robust performance and high safety through the use of aramid fibers for reinforcement and a FireRes® jacket for excellent flame retardancy.

Properties:

- Fibers: Optionally 2 or 4 BendBrightXS fibers
- Reinforcement: Aramid fibers for increased stability and protection
- Jacket: FireRes® jacket for outstanding flame retardancy
- Fire behavior class (according to EN 13501-6): Dca - High flame retardancy
- Smoke development class (according to EN 13501-6): s2 - Low smoke development
- Euroclass flaming droplets (according to EN 13501-6): d2 - Low flaming droplets
- Euroclass acidity (according to EN 13501-6): a1 - No acid formation

This datasheet was created automatically on 17-09-2026 . Technical changes reserved.



DATASHEET

This cable is ideal for use in demanding indoor installations where high safety and performance requirements must be met.

Delivery: 500m spool

Tekniske egenskaber

Available variants

ArtNr.	Bezeichnung	Unique				
FTTH-IDROP900-2-D		Unique				
FTTH-IDROP900-4-D		Dca	4.5 mm	OS2	4	500 N
FTTH-IDROP900-4-D-B		Dca	4.5 mm	OS2	4	500 N

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 17-09-2026 . Technical changes reserved.

