

DATASHEET



General data

Fiber Optical flush-mounted data outlet to accommodate 2 SC-Simplex adapter or 2 LC-Duplex adapter. The data outlet is equipped with couplings in the classes OM3, OM4 or OS2 including shutter. **The highlight of this flush-mounted data outlet is that it not only has an integrated receptacle for excess fiber lengths, but also has a receptacle for splice protection (4x crimp or 4x shrink).** Depending on the application, the holder can also be dismantled so that it does not get in the way when pre-assembled cables are installed.

Performance features:

- Horizontal and vertical installation in the cable duct or flush mounting
- Recording of fiber overlengths
- Integrated splice protection for 4 splices
- Cover 80mm x 80mm
- Data outlet depth of 40mm for installation in flush-mounted boxes or cavity wall boxes

This datasheet was created automatically on 12-09-2026 . Technical changes reserved.

DATASHEET

Tekniske egenskaber

Available variants

ArtNr.	Bezeichnung	Colour	RAL-number
FTTH-OUTLET-SC-OM3		weiß	9010

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 12-09-2026 . Technical changes reserved.

