

DATASHEET



General data

Transmits data from 10/100Base-TX copper to fiber interfaces
 SC single-mode fiber optic connector for transmission up to 20 km
 Integrated LFP (Link Fault Pass-through) (LLCF/LLR) technology
 IEEE-802.3x flow control protects against packet loss and ensures reliable data transmission
 Toggle switch for configuration adjustment
 Supports transmission with a short time delay
 Supports transmission of extra-long packets up to 1.6 kB
 Operating temperature range of -10°C to 55°C

The FVT-2201 SMF SC media converter can convert network signals between copper and fiber-based networks. The converter is equipped with a 10/100Base-TX RJ-45 port, supports full-duplex and half-duplex switch connectivity and 10Base-T and 100Base-TX automatic detection. When used in multi-mode with fiber optic cabling, the network range can be extended up to 20 km.

The device has integrated dip switches for easy converter configuration, is based on the intelligent LFP (Link Fault Pass-through), which means the converter can monitor both fiber optic and copper connections for signal loss.

The FVT-2201 can work at temperatures from -10° to 55° Celsius. The converter can be used as a standalone system or as a plug-in module in the CHV-2000 19-inch converter rack, which can hold up to 14 devices for use in a central distribution cabinet.

Port configuration
 Fast Ethernet RJ45 1

general
 Color: Black

This datasheet was created automatically on 18-09-2026 . Technical changes reserved.



DATASHEET

Miscellaneous

Data rate Fast Ethernet
Fiber Optical Mode Single Mode
Media Interface RJ45 to SMF SC
Manageable No
Grade Commercial

Others

Operating humidity 5% RH ~ 90% RH
Operating temperature -10°C ~ 55°C
Scope of delivery Power adapter,
Quick Installation Guide

Physical Specifications

Dimensions (W x D x H) 94 x 70 x 25 mm
Product weight (kg) 0.42

System specifications

indicator PWR,
TX (FDX, 100, Link/Act),
FX (100, Link/Act)
Standards IEEE 802.3 10-BASE-T, Ethernet,
IEEE 802.3u 100-BASE-TX, Fast Ethernet,
IEEE 802.3x Flow Control (full-duplex flow control)
Wavelength (nm) 1310

Tekniske egenskaber

Available variants

ArtNr.	Bezeichnung	Unique
FVT-2201		Unique

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 18-09-2026 . Technical changes reserved.

