DATASHEET

16mm Conduit Flexible PVC 750N grey



General data

FXP FLexible Conduit light gauge
Corruguated
high temparature range -45 - +60 Degree
Coils of 50 mtr
Coils of 25 mtr for 32-63mm conduits
In accordance with IEC/EN 61386-22, IEC60423
PVC-U, cilikone free
750N

Tekniske egenskaber

Available variants

ArtNr.	Bezeichnung	Colour	Halogen free	Inner diameter	Material	Outer diameter
FXPT16 GR	16mm Conduit Flexible PVC 750N grey	grey	False	10.7 mm	PVC-U	16 mm
FXPT20 GR	20mm Conduit Flexible PVC 750N grey	grey	False	14.1 mm	PVC-U	20 mm
FXPT25 GR	25mm Conduit Flexible PVC 750N grey	grey	False	18.3 mm	PVC-U	25 mm

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 20-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION