DATASHEET









General data

8x 10/100/1000 Mbps PoE ports and 2x 1000 Mbps SFP ports, Layer 2 network management
180W total PoE power budget, up to 2 ports at 90W (ports 1, 2), 6 ports at 30W, or 8 ports at 15.4W
IEEE 802.3af/at/bt PoE compliant for easy deployment and installation.
Supports web configuration for PoE management, QoS, VLAN, MSTP, multi-broadcast, and port management
6KV surge protection, 6KV contact / 8KV air ESD protection.

Tekniske egenskaber

Available variants

ArtNr.	Bezeichnung	Max. PoE power
GEP-1061		180 W

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 15-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION