

DATASHEET



General data

24 Gigabit PoE ports, 2 Gigabit RJ45 uplink ports and 2 Gigabit SFP uplink slots
 375W PoE budget, up to 2 90W ports (Port 1 and 2) and up to 22 30W ports
 IEEE 802.3af/at/bt PoE compliant for easy deployment and installation
 Supports port-based VLAN
 Supports IEEE 802.1P Layer 2 priority queuing for optimal data flow

The LevelOne GEP-2841 Web Smart Gigabit PoE Switch offers 24 10/100/1000Base-T PoE ports, 2 Gigabit Uplink SFP ports and 2 Gigabit Uplink RJ45 ports for a high-speed network. Highly visible status LEDs allow for easy monitoring of port link activity. Additionally, the SFP slots support pluggable modules, allowing you to choose from a variety of transceivers. It offers powerful advanced PoE functionality and a total PoE budget of 375W. It is fully compliant with the IEEE802.3af/at/bt PoE standard with a maximum power budget of 90W (on ports 1 and 2). It supports up to 30W output power per additional PoE port, giving you power distribution flexibility for a wide range of PoE PD devices. This can significantly reduce infrastructure cabling costs as there is no need for electrical cabling, meaning less UPS is required.

General
 Color: Black

Features

VLAN:

- Static VLAN
- Port-based VLAN

QoS:

- Priority selection
- DSCP remapping
- Priority to queue
- Port-based priority

This datasheet was created automatically on 08-10-2026 . Technical changes reserved.



DATASHEET

● Packet scheduling

Monitoring:

- Port Statistics Information
- IGMP Setting(Enable/Disable),
- Trunk Group Setting,
- Port based mirroring,
- port isolation,
- Bandwidth Control,
- jumbo frame,
- Loop detection and prevention
- Management ● WEB (HTTP)
- Software upgrade
- Configuration export/import
- PoE port management
- Security MAC Address:
- Static MAC
- Mac constraint
- storm control,
- DHCP control

Miscellaneous

Grade Commercial
Data rate Gigabit Ethernet
PoE Supported Yes
Manageable Yes
Fanless No
Concurrent ports 28.00 ports
PoE power budget 375.00 watts

Others

Approvals and Compliance

- CE
- RoHS
- Operating humidity 5% RH ~ 90% RH
- Operating temperature -10°C ~ 65°C
- Storage humidity 5% RH ~ 95% RH
- Storage temperature -40°C ~ 75°C
- Scope of delivery ● GEP-2841
- Power cord
- 19" Rack Mount Kit
- Quick Installation Guide
- Declaration of Conformity

Physical Specifications

Product weight (kg) 2,712 kg

This datasheet was created automatically on 08-10-2026 . Technical changes reserved.



EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION



DATASHEET

Dimensions (W x D x H) 440 x 220 x 45 mm

System specifications

Energy consumption ● 25W (without PoE)

● 400W (full loading PoE on)

Standards ● IEEE 802.3 10-BASE-T, Ethernet

● IEEE 802.3u 100-BASE-TX, Fast Ethernet

● IEEE 802.3ab 1000Base-T Gigabit Ethernet

● IEEE 802.3z 1000Base-X Gigabit Ethernet

● IEEE802.3x Flow Control and Back Pressure

● IEEE802.3af

● IEEE802.3at

● IEEE802.3bt

Power supply 100-240VAC, 50-60Hz, 4.8A

Pin assignment and polarity 1/2 (+), 3/6 (-)

Attachment 19" rack mount, desk mount

Flash memory size 8 MB

Memory size 256K

MAC address table 8K

Jumbo frames (KB) 9 KB

Micro switch WEB Management (Enable/Disable)

Packet buffer 40.32 Mpps

Backplane (Gbit/s) 56 Gbps

Tekniske egenskaber

Available variants

ArtNr.	Bezeichnung	Max. PoE power
GEP-2841		375 W

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 08-10-2026 . Technical changes reserved.

