

DATASHEET



General data

Short description

- 24 PoE-Plus Gigabit Ethernet ports support PoE Watchdog and 4 Gigabit SFP/RJ45 combo
- PoE total power budget: 380W, up to 30W per port
- IEEE 802.3af/at PoE compliant to simplify deployment and installation
- Supports 8K MAC address auto-learning and auto-aging
- 9K jumbo frames to increase data transfer rates
- IP multicast filtering through IGMP Snooping V1/V2
- 802.1Q Tag-based VLAN enables network segmentation to improve performance and security
- IEEE 802.1p QoS with 4 priority queues
- Supports storm control for unknown unicast/broadcast/multicast
- Minimizes carbon footprint with energy efficient technology (IEEE 802.3az)
- 4KV surge protection, 6KV contact / 8KV air ESD protection
- Web-based Smart Lite real-time management
- Supports LevelOne IP Locator for easier IP management.

Description

The LevelOne Hilbert GES-2128P Gigabit PoE Smart Lite Switch is a new generation Ethernet switch that offers powerful PoE functionality and ease of use, enabling Ethernet services cost-effectively over copper connections. The GES-2128P offers 24 (10M/100M/1G) RJ45 PoE+ (support 802.3at/af, and up to 380W total) ports and 4 Gigabit combo RJ45/SFP slots. With the new LevelOne IP Locator, the simple switch discovery software, all Hilbert series switches can be searched and information about the switch and IP configuration can be displayed. It is compatible with the most common Windows and Mac operating systems.

The LevelOne GES-2128P offers high hardware performance and environmental flexibility for businesses. The GES-2128P is ideal for easy management, optimal usability and lower total cost of ownership.

Further information

- Approvals and Compliance ● CE ● UKCA ● FCC Part 15, Subpart B Class B ● RoHS

This datasheet was created automatically on 08-10-2026 . Technical changes reserved.



DATASHEET

- Embedded system SoC
- Acoustic noise (dB): 30 dB (A)
- Packet buffer: 4.1 Mbits
- Display: Power, System, Link/Act, PoE
- Jumbo frames (KB): 9K
- MAC address table: 8K
- Flash memory size: 2MB
- Mounting: 19" rack mount, desk mount
- Pin assignment and polarity: 1/2 (+), 3/6 (-)
- Power supply: 100-240 VAC, 50-60 Hz
- Standards:
 - IEEE 802.3 10-BASE-T (Ethernet) ● IEEE 802.3u 100-BASE-TX (Fast Ethernet) ● IEEE 802.3ab 1000BASE-T (Gigabit Ethernet) ● IEEE 802.3z 1000BASE-X (Gigabit Ethernet) ● IEEE 802.3x Flow Control (full-duplex flow control) ● IEEE 802.3af Power over Ethernet (PoE) ● IEEE 802.3at Power over Ethernet Plus (PoE+) ● IEEE 802.3az: Energy Efficient Ethernet
- Port configuration: 28
- Basic functions
 - L2 switching functions ● IGMP snooping ● Link Aggregation (Supports static link aggregation) ● Port Mirroring ● Kabltest VLAN ● Supports up to 32 VLANs (from 4K VLAN IDs) ● MTU/Port/802.1Q VLAN Quality of Service (QoS) ● Supports port-based/802.1p/DSCP priority ● Supports 4 priority queues ● Rate Limit ● Storm Control
- Management ● Web based Graphical User Interface (GUI) ● Supports LevelOne IP Locator for easier IP management.
- Product weight (kg): 3.4 kg
- Color: Black
- Scope of delivery ● GES-2128P ● Power cable ● 19" rack mounting kit ● Quick Installation Guide ● Declaration of Conformity
- Switching performance: 56 Gbps
- PoE supported: Yes
- Total concurrent ports: 28
- PoE Power Budget 380.00 Total
- Energy consumption: 400W (full loading/PoE on)
- Heat dissipation: 88.71 (Btu/H)
- MTBF: 43,800 hours

Tekniske egenskaber

Available variants

ArtNr.	Bezeichnung	Max. PoE power
GES-2128P		380 W

This datasheet was created automatically on 08-10-2026 . Technical changes reserved.



DATASHEET

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 08-10-2026 . Technical changes reserved.

