DATASHEET







General data

20x Gigabit-Ethernet SFP Slots with 4x 1G RJ45-SFP Combo Slots1 and 4x 10Gigabit SFP+ slots, additionally there is 1x RJ45 MGMT Port and 1x RJ45 Console Port
The SFP slot supports 1G MGBICs, the SFP+ slot supports MGBIC for 10Gigabit 10GBaseX
Management: SNMP, WEB, RMON, Telnet und TFTP administration
IPv6, Multicast, VLAN, Virtual Stacking, Autonegotiation and Auto MDI/MDIX and much more.
L3 Features: Multi-netting (CIDR), IPv4 Static Routes, RIP v1/v2,. ARP/Proxy ARP
19“ Mounting brackets included
Metal housing with fan (L x W x H): 440 x 220 x 44 mm

Tekniske egenskaber

Available variants

ArtNr.	Bezeichnung	Unique
GTL-2872		Unique

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product’s suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 05-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION