DATASHEET







General data

28x Gigabit-Ethernet-Ports with 2x 10Gigabit SFP+ slots, additionally there is an extension slot for an 10G module
SFP+ slot supports MGBIC for 10Gigabit 10GBaseX,
Management: SNMP, WEB, RMON, Telnet
IPv6, Multicast, VLAN, Virtual Stacking, OAM, ERPS and much more.
L3 Features: Multi-netting (CIDR), IPv4 Static Routes, RIP v1/v2,. ARP/Proxy ARP
Hardware stacking up to 8 devices
19“ Mounting brackets included
Metal housing (L x W x H): 440 x 315 x 44 mm

Tekniske egenskaber

Available variants

ArtNr.	Bezeichnung	Unique
GTL-2891		Unique

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product’s suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 24-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION