DATASHEET







General data

24x Gigabit PoE Ports + 4x 10-Gigabit SFP+ slots
SFP+ slots support MiniGBICs for 10Gigabit 10GBaseX
PoE: IEEE-802.3af / at PoE compliance with PoE detection
IEEE-802.1d/w/s Spanning Tree Protocol (STP) and Port mirroring
Management: SNMP, WEB, RMON, Telnet and TFTP management
Features: IPv4/IPv6, port-based VLAN, IEEE 802.1Q VLAN-tagging and GVRP
IP Multicast Filtering with IGMP Snooping V1 / V2 / V3
L3 Features: Static Route, DHCP Server, ARP
Port-based IEEE-802.1X-authentification over access list (ACL) with over 512 entries
IEEE 802.3ad LACP for automatic port-aggregation
Metal housing (W x D x H): 442 x 221 x 44 mm

Tekniske egenskaber

Available variants

ArtNr.	Bezeichnung	Max. PoE power
GTP-2881		185 W

Note on Intended Use

This datasheet was created automatically on 25-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 25-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION