

DATASHEET

Power Supply 24V, 0.63A, 15.2W, Mean Well



General data

Power supply unit for the top-hat rail for operating e.g. Industrial switching

plastic housing, step shape

1Ø, full range input

compact size, 1SU ~ 6SU width (DIN EN43880)

insulation class II

adjustable DC output voltage

idle current consumption <0, 3W

Mount on industrial rails TS-35 / 7.5 or 15

Suitable for building automation and control of household appliances

Tekniske egenskaber

Available variants

ArtNr.	Bezeichnung	Max. output current 1	Power output
HDR-15-24	Power Supply 24V, 0.63A, 15.2W, Mean Well	0.63 A	15 W
HDR-30-24	Power Supply 24V, 1.5A, 30W, Mean Well	1.5 A	30 W
HDR-100-24		4.2 A	100 W

This datasheet was created automatically on 09-10-2026 . Technical changes reserved.



DATASHEET

Power Supply 24V, 0.63A, 15.2W, Mean Well

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 09-10-2026 . Technical changes reserved.

