

DATASHEET

20mm Conduit Flexible LSZH 320N grey



General data

HFX FLeXible Conduit light gauge
 Corrugated
 Delivered in Light Grey or White
 Coils of 50 mtr for 16-25mm conduit
 Coils of 25 mtr for 32-63mm conduits
 In accordance with IEC/EN 61386-22, IEC60423, LSFoH Low smoke - zero Halogen
 320N

Tekniske egenskaber

Available variants

ArtNr.	Bezeichnung	Colour	Halogen free	Impact strength	Inner diameter	Material	Outer diameter
HFX16 HG	16mm Conduit Flexible LSZH 320N grey	grey	True	320 Newton	11.4 mm	PP Blend	16 mm
HFX20 HG	20mm Conduit Flexible LSZH 320N grey	grey	True	320 Newton	13.5 mm	PP Blend	20 mm
HFX25 HG	25mm Conduit Flexible LSZH 320N grey	grey	True	320 Newton	17.5 mm	PP Blend	25 mm

This datasheet was created automatically on 14-10-2026 . Technical changes reserved.



DATASHEET

20mm Conduit Flexible LSZH 320N grey

HFX40 HG	40mm Conduit Flexible LSZH 320N grey	grey	True	320 Newton	30 mm	PP Blend	40 mm
HFX50 HG	50mm Conduit Flexible LSZH 320N grey	grey	True	320 Newton	38.5 mm	PP Blend	50 mm
HFX63 HG	63mm Conduit Flexible LSZH 320N grey	grey	True	320 Newton	54.1 mm	PP Blend	63 mm
HFXS16 SW	16mm protective hose, black, LSF0H	black	True	320 Newton	11.5 mm	PP Blend	16 mm
HFXS20 SW	20mm protective hose, black, LSF0H	black	True	320 Newton	13.5 mm	PP Blend	20 mm
HFXS25 SW	25mm protective hose, black, LSF0H	black	True	320 Newton	17.5 mm	PP Blend	25 mm
HFXS40 SW	40mm protective hose, black, LSF0H	black	True	320 Newton	30 mm	PP Blend	40 mm

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 14-10-2026 . Technical changes reserved.

