DATASHEET

12mm Flex conduit, halogen-free black 750N, UV-resistant, High temperature



General data

HFX FLexible Conduit light gauge
Corruguated
high temparature range -45 - +150 Degree
Coils of 50 mtr for 16-25mm conduit
Coils of 25 mtr for 32-63mm conduits
In accordance with IEC/EN 61386-22, IEC60423, LSFoH Low smoke - zero Halogen
750N

Tekniske egenskaber

Available variants

ArtNr.	Bezeichnung	Colour	Halogen free	Impact strength	Inner diameter	Material	Operating temperature	Outer diameter
HFXP-HT 12 SW	12mm Flex conduit, halogen-free black 750N, UV-resistant, High temperature	black	True	750 Newton	9 mm	PC	-45 – 150	13 mm
HFXP-HT 20 SW	20mm Flex conduit, halogen-free black 750N, UV-resistant, High temperature	black	True	750 Newton	14.1 mm	PC	-45 – 150	20 mm

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 20-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION